

Medium induction heater TIM 100 M High heating capacity of up to 120 kg bearing

Medium induction heater [TIM 100M](#)

High heating capacity of up to 120 kg bearing

The SKF medium induction heater TIH 100m has the same high standards of efficiency and performance as the smaller heater [TIH 030m](#), combined with increased capacity. The advanced design of the power electronics allows features of accurate electric current control, cut-outs to avoid overheating, controls on rate of temperature increase, these are as some of the standard features in the TIH...m range.

Placing the induction coil outside the heater's housing allows the heating of bearings weighing up to 120 kg (264 lb). The heater is equipped with thermal overheating protection to reduce the risk of damage to the induction coil and the electronics. In addition to temperature mode, the TIH 100m is equipped with a time mode for heating components other than bearings. The heater is supplied standard with three yokes and is available in two executions: [230V/50-60Hz](#) or [400-460V/50-60Hz](#).

Features and benefits

Standard swivel arm for large size yoke

- Capable of heating a 97 kg (213 lb) bearing in less than 20 minutes, saving time and energy
- 2-step power setting and smaller yokes allow heating smaller bearings safely and at lower power consumption
- Temperature mode pre-set at 110 °C (230 °F) to help prevent bearing over-heating
- Automatic demagnetisation